

The regulation forecast is subject to change daily as actual events occur.
Forecasted release reductions or increases are subject to change based on forecasted temperature and river conditions
and releases may be adjusted during winter freeze-in period. Intrasystem regulation may also require release adjustments.

		REGULATION FORECAST: 06/13/18																												
		FTPK				GARR				OAHE				BEND				FTRA				GAPT				SYSTEM				
		24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	GE	SG	DSG		
W	13	2246.0	24.5	20.0	3.90	1850.3	84.1	44.0	12.98	1611.9	46.9	39.5	12.06	1420.5	39.5	41.0	4.47	1356.7	46.0	43.0	5.34	1206.5	44.7	44.0	2.68	41.42	65194	100	W	13
T	14	2246.0	24.0	20.0	3.90	1850.5	82.1	44.0	13.00	1611.9	47.0	39.5	12.07	1420.5	39.5	41.0	4.46	1356.7	45.1	42.0	6.39	1206.6	44.9	44.0	2.68	42.49	65291	96	T	14
F	15	2246.0	23.0	20.0	3.90	1850.7	80.9	44.0	13.01	1612.0	47.1	41.0	12.52	1420.5	41.0	41.0	4.46	1356.8	44.4	41.0	6.39	1206.6	44.4	44.0	2.68	42.96	65383	92	F	15
	16	2246.0	22.0	20.0	3.90	1850.8	72.4	44.0	13.02	1612.0	47.3	38.0	11.62	1420.6	38.0	33.0	3.58	1356.7	36.3	41.0	6.39	1206.5	43.4	44.0	2.68	41.19	65454	71		16
	17	2246.0	21.0	20.0	3.08	1851.0	69.1	44.0	13.03	1612.1	47.4	36.0	11.02	1421.0	36.0	25.0	2.70	1356.4	28.1	41.0	6.37	1206.4	43.0	44.0	2.67	38.88	65515	62		17
M	18	2246.0	20.5	20.0	3.08	1851.1	65.7	44.0	13.04	1612.1	47.5	39.0	11.93	1420.9	39.0	42.0	4.59	1356.5	44.9	41.0	6.38	1206.3	43.0	44.0	2.67	41.68	65569	54	M	18
T	19	2246.0	20.0	20.0	3.08	1851.2	65.9	44.0	13.05	1612.2	47.5	39.0	11.93	1420.8	39.0	42.0	4.58	1356.5	44.8	41.5	6.38	1206.2	43.0	44.0	2.66	41.68	65621	52	T	19
W	20	2246.0	19.0	20.0	3.08	1851.3	64.2	44.0	13.05	1612.2	47.5	39.0	11.94	1420.7	39.0	42.0	4.58	1356.6	44.8	41.5	6.38	1206.2	43.3	44.0	2.66	41.69	65668	47	W	20
T	21	2246.0	18.1	20.0	3.08	1851.4	61.7	44.0	13.06	1612.2	47.5	39.0	11.94	1420.6	39.0	42.0	4.58	1356.7	44.7	41.5	6.39	1206.1	43.5	44.0	2.66	41.70	65709	41	T	21
F	22	2245.9	17.1	20.0	3.08	1851.5	61.4	44.0	13.07	1612.3	47.5	39.0	11.94	1420.4	39.0	42.0	4.57	1356.7	44.7	41.5	6.39	1206.1	43.5	44.0	2.65	41.70	65747	38	F	22
	23	2245.9	16.6	20.0	3.08	1851.5	59.2	44.0	13.07	1612.3	47.5	38.0	11.64	1420.6	38.0	33.0	3.58	1356.6	35.6	42.0	6.38	1206.0	43.5	44.0	2.65	40.41	65778	31		23
	24	2245.9	16.0	20.0	3.08	1851.6	57.6	44.0	13.08	1612.4	47.5	36.0	11.04	1421.0	36.0	25.0	2.70	1356.3	27.6	42.0	6.37	1206.0	43.8	44.0	1.92	38.19	65805	28		24
M	25	2245.8	15.4	18.0	3.08	1851.7	56.0	44.0	13.08	1612.5	47.5	39.0	11.95	1420.9	39.0	42.0	4.59	1356.3	44.5	42.0	6.37	1206.0	44.0	44.0	1.92	40.99	65833	28	M	25
T	26	2245.8	14.8	18.0	3.08	1851.7	53.2	44.0	13.09	1612.5	47.5	39.0	11.95	1420.7	39.0	42.0	4.59	1356.3	44.5	42.5	6.37	1206.0	44.0	44.0	1.92	41.00	65853	20	T	26
W	27	2245.8	14.3	18.0	3.08	1851.7	49.2	44.0	13.09	1612.5	47.5	39.0	11.96	1420.6	39.0	42.0	4.59	1356.4	44.5	42.5	6.37	1206.0	44.2	44.0	1.92	41.00	65864	11	W	27
T	28	2245.7	13.9	18.0	3.07	1851.7	46.7	44.0	13.09	1612.6	47.5	39.0	11.96	1420.5	39.0	42.0	4.59	1356.4	44.5	42.5	6.37	1206.0	44.4	44.0	1.92	41.01	65870	6	T	28
F	29	2245.7	13.5	18.0	3.89	1851.7	43.2	44.0	13.09	1612.6	47.5	39.0	11.96	1420.4	39.0	42.0	4.59	1356.5	44.5	42.5	6.38	1206.0	44.3	44.0	1.92	41.83	65868	-2	F	29
	30	2245.6	13.2	18.0	3.89	1851.7	42.0	44.0	13.09	1612.7	47.5	38.0	11.66	1420.6	38.0	33.0	3.60	1356.3	35.5	42.5	6.37	1206.0	44.2	44.0	1.92	40.53	65863	-5		30
	1	2245.6	12.9	18.0	3.89	1851.7	40.8	44.0	13.09	1612.7	43.7	36.0	11.06	1420.9	36.0	25.0	2.71	1355.9	25.7	42.5	6.35	1206.0	44.1	44.0	1.92	39.02	65846	-16		1
M	2	2245.5	12.7	18.0	3.89	1851.7	40.8	44.0	13.08	1612.8	43.7	39.0	11.97	1420.8	39.0	42.0	4.61	1355.9	42.7	42.5	6.35	1206.0	44.0	44.0	1.92	41.83	65829	-17	M	2
T	3	2245.5	12.5	16.0	3.89	1851.7	40.8	44.0	13.08	1612.8	43.7	39.0	11.97	1420.7	39.0	42.0	4.61	1355.9	42.7	42.5	6.35	1206.0	44.0	44.0	1.92	41.83	65816	-13	T	3
W	4	2245.4	12.4	16.0	3.89	1851.6	40.7	44.0	13.08	1612.8	43.7	39.0	11.97	1420.6	39.0	42.0	4.61	1355.9	42.7	42.5	6.35	1206.0	43.9	44.0	1.92	41.82	65802	-14	W	4
T	5	2245.4	12.3	14.0	3.89	1851.6	40.2	44.0	13.08	1612.8	43.7	39.0	11.97	1420.5	39.0	42.0	4.61	1355.9	42.7	42.5	6.35	1206.0	43.8	44.0	1.92	41.82	65791	-11	T	5
F	6	2245.4	12.3	14.0	3.88	1851.6	39.4	44.0	13.08	1612.9	43.7	37.0	11.37	1420.3	37.0	42.0	4.61	1355.9	42.7	42.5	6.35	1206.0	43.8	44.0	1.92	41.22	65777	-13	F	6

Project:		System:		Units:	
24EL	Midnight Elevation (feet above sea level)	GE	Daily Power Generation (1000 MWh)	kcfs	thousand cubic feet per second
24ID	Daily Average Inflow (kcfs)	SG	Midnight Storage (kAF)	MWh	megawatt hour
24OD	Daily Average Release (kcfs)	DSG	Daily Storage Change (kAF)	kAF	thousand acre feet
24GE	Daily Power Generation (1000 MWh)				

The midnight elevation (24EL) will be shown in color when a reservoir enters one of the following zones.
ex. 1234.5 - Exclusive Flood Control Zone (24EL)
ex. 1234.5 - Surcharge (24EL)