

The regulation forecast is subject to change daily as actual events occur.
Forecasted release reductions or increases are subject to change based on forecasted temperature and river conditions
and releases may be adjusted during winter freeze-in period. Intrasystem regulation may also require release adjustments.

		REGULATION FORECAST: 07/11/18																												
		FTPK				GARR				OAHE				BEND				FTRA				GAPT				SYSTEM				
		24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	GE	SG	DSG		
W	11	2247.8	16.1	18.0	4.09	1853.1	56.0	60.0	12.99	1615.9	61.9	44.0	13.70	1420.0	44.0	41.0	4.24	1361.3	46.0	52.0	6.62	1205.8	51.4	50.0	2.64	44.28	68418	11	W	11
T	12	2247.7	15.5	18.0	4.09	1853.0	53.0	60.0	12.99	1616.0	61.7	44.0	13.71	1420.1	44.0	41.0	4.25	1361.1	46.0	52.0	6.62	1206.0	52.2	50.0	2.65	44.30	68424	6	T	12
F	13	2247.7	14.9	18.0	4.09	1853.0	51.6	60.0	12.98	1616.1	61.5	44.5	13.86	1420.3	44.5	39.0	4.05	1360.9	44.0	52.0	6.61	1206.1	52.7	51.0	2.66	44.25	68424	0	F	13
	14	2247.6	14.2	18.0	4.09	1852.9	50.2	60.0	12.98	1616.2	61.2	42.0	13.11	1420.5	42.0	35.0	3.63	1360.7	40.0	52.0	6.59	1206.2	52.6	52.0	2.66	43.05	68417	-7		14
	15	2247.6	13.6	18.0	4.09	1852.8	48.9	60.0	12.97	1616.3	61.0	40.0	12.50	1421.0	40.0	26.0	2.68	1360.2	31.0	54.0	6.57	1206.1	52.5	53.0	2.65	41.47	68400	-17		15
M	16	2247.5	13.0	18.0	4.09	1852.8	47.6	60.0	12.97	1616.4	60.8	46.0	14.34	1420.9	46.0	49.0	5.17	1360.1	54.0	55.0	6.56	1206.1	53.6	54.0	2.65	45.78	68377	-23	M	16
T	17	2247.5	12.4	18.0	4.09	1852.7	46.3	60.0	12.96	1616.5	60.7	46.0	14.35	1420.8	46.0	49.0	5.17	1360.1	54.0	56.0	6.56	1206.0	54.9	55.0	2.65	45.78	68349	-28	T	17
W	18	2247.4	11.8	18.0	4.09	1852.6	45.0	60.0	12.96	1616.5	60.5	46.0	14.35	1420.7	46.0	49.0	5.17	1360.0	53.9	56.0	6.56	1206.0	55.8	56.0	2.65	45.77	68316	-33	W	18
T	19	2247.4	11.2	18.0	4.08	1852.5	43.7	60.0	12.95	1616.6	60.4	46.0	14.36	1420.6	46.0	49.0	5.18	1359.9	53.9	57.5	6.55	1206.0	56.1	56.0	2.65	45.77	68277	-39	T	19
F	20	2247.3	10.6	18.0	4.08	1852.4	42.4	60.0	12.94	1616.7	60.2	46.0	14.36	1420.5	46.0	49.0	5.18	1359.8	53.9	57.5	6.55	1206.0	57.3	57.0	2.65	45.77	68234	-43	F	20
	21	2247.2	10.0	18.0	4.08	1852.3	41.5	60.0	12.93	1616.8	60.1	44.0	13.76	1420.6	44.0	40.0	4.22	1359.5	44.9	59.5	6.53	1206.0	58.0	58.0	2.65	44.18	68183	-51		21
	22	2247.1	9.7	18.0	4.08	1852.2	40.3	60.0	12.93	1616.9	60.0	42.0	13.15	1421.0	42.0	30.0	3.16	1358.9	34.8	59.5	6.50	1206.0	59.2	59.0	2.65	42.48	68129	-54		22
M	23	2247.0	9.4	18.0	4.08	1852.1	39.1	57.0	12.92	1616.9	59.9	52.0	16.02	1420.9	52.0	55.0	5.88	1358.9	59.6	59.5	6.50	1206.0	60.0	60.0	2.65	48.06	68077	-52	M	23
T	24	2247.0	9.2	18.0	4.08	1852.0	38.0	57.0	12.91	1616.9	58.3	52.0	16.02	1420.8	52.0	55.0	5.89	1358.9	59.4	59.5	6.50	1206.0	60.0	60.0	2.65	48.05	68019	-58	T	24
W	25	2246.9	8.9	18.0	4.08	1851.9	36.8	57.0	12.90	1616.9	57.0	52.0	16.03	1420.7	52.0	55.0	5.89	1358.9	59.2	59.5	6.50	1206.0	60.0	60.0	2.65	48.04	67955	-64	W	25
T	26	2246.8	8.6	16.0	4.07	1851.8	35.6	54.0	12.90	1617.0	56.8	52.0	16.03	1420.6	52.0	55.0	5.89	1358.9	59.1	59.5	6.50	1206.0	60.0	60.0	2.65	48.03	67898	-57	T	26
F	27	2246.7	8.3	16.0	4.07	1851.7	34.4	54.0	12.89	1617.0	55.2	52.0	16.03	1420.5	52.0	55.0	5.89	1358.8	58.9	59.5	6.50	1206.0	60.0	60.0	2.65	48.03	67834	-64	F	27
	28	2246.6	8.0	16.0	4.07	1851.5	32.7	54.0	12.88	1617.0	53.9	50.0	15.60	1420.6	50.0	46.0	4.92	1358.6	49.7	59.5	6.49	1206.0	60.0	60.0	2.65	46.61	67763	-71		28
	29	2246.6	7.8	16.0	4.07	1851.4	31.2	54.0	12.87	1617.0	53.7	48.0	15.00	1421.0	48.0	36.0	3.85	1358.2	39.6	59.5	6.46	1206.0	60.0	60.0	2.65	44.90	67688	-75		29
M	30	2246.5	7.7	16.0	4.07	1851.3	30.4	54.0	12.86	1617.0	53.7	52.0	16.03	1420.9	52.0	55.0	5.93	1358.1	58.4	59.5	6.46	1206.0	60.0	60.0	2.65	48.00	67610	-77	M	30
T	31	2246.4	7.6	16.0	4.07	1851.1	29.8	54.0	12.85	1617.0	53.7	52.0	16.03	1420.8	52.0	55.0	5.94	1358.1	58.2	60.0	6.46	1206.0	60.0	60.0	2.65	47.99	67530	-80	T	31
W	1	2246.3	7.5	16.0	4.06	1851.0	29.4	53.0	12.84	1617.0	53.6	52.0	16.03	1420.7	52.0	55.0	5.94	1358.0	58.0	60.0	6.46	1206.0	60.3	60.0	2.65	47.98	67451	-79	W	1
T	2	2246.2	7.4	16.0	4.06	1850.9	29.1	53.0	12.83	1617.0	53.1	52.0	16.03	1420.6	52.0	55.0	5.94	1358.0	57.9	59.5	6.45	1206.0	60.5	60.0	2.65	47.97	67371	-80	T	2
F	3	2246.1	7.2	16.0	4.06	1850.7	28.8	53.0	12.82	1617.0	52.7	52.0	16.03	1420.5	52.0	55.0	5.94	1357.9	57.7	59.5	6.45	1206.0	60.2	60.0	2.65	47.96	67288	-83	F	3

Project:		System:		Units:	
24EL	Midnight Elevation (feet above sea level)	GE	Daily Power Generation (1000 MWh)	kcfs	thousand cubic feet per second
24ID	Daily Average Inflow (kcfs)	SG	Midnight Storage (kAF)	MWh	megawatt hour
24OD	Daily Average Release (kcfs)	DSG	Daily Storage Change (kAF)	kAF	thousand acre feet
24GE	Daily Power Generation (1000 MWh)				

The midnight elevation (24EL) will be shown in color when a reservoir enters one of the following zones.
ex. 1234.5 - Exclusive Flood Control Zone (24EL)
ex. 1234.5 - Surcharge (24EL)